




Jack Nut

Material Low Carbon Steel

Finish : Zinc Clear Cr3

Jack Nuts are a unique series of threaded insert designed for use in light duty, thin, or fragile materials. When installed, the body of the Jack Nut collapses to form a large footprint which provide a durable grip on blind side. Jack Nuts can be installed into slightly oversized holes, uneven surfaces and won't distort the material including soft plastics.



Part Number	Thread	Grip Range		A	B	C	D
RNJK-0401	M4	0.0-5.0		8.50	16.80	12.20	1.60
RNJK-0402	M4	5.0-10.0		8.50	22.00	12.20	1.60
RNJK-0501	M5	0.0-5.0		10.50	18.40	14.00	1.60
RNJK-0502	M5	5.0-10.0		10.50	23.20	14.00	1.60
RNJK-0601	M6	0.0-5.0		12.00	18.60	16.00	1.60
RNJK-0602	M6	5.0-10.0		12.00	22.90	16.00	1.60
RNJK-0801	M8	0.0-5.0		15.50	19.00	18.00	1.80
RNJK-0802	M8	5.0-8.0		15.50	24.00	18.00	1.80
RNJK-0601-14	1/4"	0.0-5.0		11.00	18.60	16.00	1.60

Diagrams and Drawings are for measuring purposes only. Dimensions and specifications are subject to change without notice. The test data provides approximate strength values averaged in multiple tests in various materials and thicknesses.