




Rivnut
Fastening Systems

1300 887 341
sales@rivnut.com.au
Unit 3, 57 Boyland Avenue,
Coopers Plains, Qld 4108

Plus Nut



Material Low Carbon Steel

Finish Zinc Plated

Optimal for high push-out applications. Straight metric hole sizes. Splined body improves torque-to-turn resistance

Part Number	Thread	Grip Range	Hole Size	A	B	C	D
RN-PNS-0504	M5	0.5-4.45	7.5	7.47	22	12.7	0.96
RN-PNS-0508	M5	4.45-8.1	7.5	7.47	24.8	12.7	0.96
RN-PNS-0607	M6	0.5-7.1	10	8.79	26.9	15.9	1.5
RN-PNS-0613	M6	7.10-12.7	10	8.79	32.8	15.9	1
RN-PNS-0807	M8	0.5-7.10	12.7	11.1	30.5	19	1.57
RN-PNS-0813	M8	7.1-12.7	12.7	11.1	36.5	19	1.57
RN-PNS-1007	M10	0.5-7.10	15.1	14.95	33.1	22.3	2.2

Thread Size	Pull-Out KN	Push-Out KN	Maximum Torque NM
M5	-	-	-
M6	12.5	5.9	22.1
M8	19.7	32	42.9
M10	-	-	-

Diagrams and Drawings are for illustrative and measuring purposes only. Dimensions and specifications are subject to change without notice. Check your distributor for the latest data sheet. The test data provides approximate strength values averaged in multiple tests in various materials and thicknesses.

www.rivnut.com.au