



Rivnut
Fastening Systems

1300 887 341
sales@rivnut.com.au
Unit 3, 57 Boyland Avenue,
Coopers Plains, Qld 4108


Rivnut Large Flange Steel - DL Series

Material Low Carbon Steel

Finish Zinc Plated



Highest resistance to vibration and spin out of all round bodied rivnuts. Flange are wide and near flush finish. Very wide grip range.



Part Number	Thread	Grip Range	Hole Size	A	L	HD	HH
RNLFSDL04	M4	0.5-2.0	6.75	6.70	11.46	9.90	0.76
RNLFSDL04-L	M4	2.0-3.3	6.75	6.70	12.70	9.90	0.76
RNLFSDL05	M5	0.5-3.3	7.6	7.50	12.85	10.55	0.76
RNLFSDL05-L	M5	3.3-5.7	7.6	7.50	15.50	10.55	0.76
RNLFSDL06	M6	0.7-4.2	10	9.92	15.50	12.70	0.76
RNLFSDL06-L	M6	4.2-6.6	10	9.92	18.00	12.70	0.76
RNLFSDL08	M8	0.7-3.8	13.5	13.45	18.40	17.40	0.76
RNLFSDL08-L	M8	3.8-7.9	13.5	13.45	21.35	17.40	0.76
RNLFSDL10	M10	0.7-3.8	13.5	13.45	18.40	17.45	0.76
RNLFSDL10-L	M10	3.8-7.9	13.5	13.45	21.20	17.45	0.76
RNLFSDL12	M12	1.6-5.1	17.5	17.45	30.40	21.98	0.76
RNLFSDL12-L	M12	5.1-8.9	17.5	17.45	34.21	21.98	0.76
RNLFSDL12-12.7	M12	8.9-12.7	17.5	17.45	38.00	21.98	0.76

Thread Size	Pull-Out KN	Push-Out	
		KN	Maximum Torque NM
M4	6.90	2.00	5.90
M5	7.80	2.90	9.80
M6	11.00	3.90	18.10
M8	20.00	6.90	29.40
M10	20.00	6.90	45.00
M12	19.90		72.00

Dimensions and specifications are subject to change without notice.

www.rivnut.com.au